

INTERACT® | Pro

Professional Conferencing Systems

A professional audio conferencing system offering TRUE stereo echo cancellation at an unbeatable market price. The INTERACT Pro platform is a complete audio system with unrivalled audio performance and application flexibility— all with simplified configuration in mind.

Directly connects to enterprise telephones, PC and HD video conferencing systems and emerging Unified Communications endpoints.



IMPROVE CLARITY
WITH TRUE
STEREO ECHO
CANCELLATION

APPLICATIONS

- + Unified Communications
- + Use with Rich-Media Systems
 - > Web Conferencing
 - > Personal Computer
 - > IP Telephony
 - > Video Conferencing
- + Telepresence
- + Board Rooms
- + Conference Rooms
- + Executive Offices

ADVANTAGES

- + Enables Unified Communication in the conference room
- + USB port connects to PC for Skype™, WebEx® and other A/V conferencing applications
- + Headset port connects to Cisco®, Avaya™, and Nortel™ handsets
- + ClearOne's HDConference and NEW true stereo AEC provides unrivalled audio quality and intelligibility
 - > Stereo Echo Cancellation for use with HD video conferencing or Telepresence
 - > Distributed Echo Cancellation® effectively eliminates echo
 - > Noise cancellation reduces background noises from fans or HVAC systems
 - > Full-duplex sound enables participants to speak and listen at the same time without cutting in and out
 - > Automatic level controls keep participants' audio balanced and consistent
 - > First-mic priority eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- + Add INTERACT Pro 8i for up to 16 microphones
- + Integral network management system enables remote configuration, control and monitoring
- + Scalable and flexible to meet most conferencing needs
 - > Add INTERACT COM for direct interface to PC or enterprise telephone sets
- + Interoperates with StreamNet® A/V over IP™ systems
- + Easy to install, program and use

> **INTERACT Pro REAR PANEL**



> **SPECIFICATIONS**

AUDIO PERFORMANCE

Conditions: Unless otherwise specified, all measurements are performed with a 20 Hz to 22 kHz BW limit (No Weighting)
 Frequency Response:
 20 Hz to 22 kHz BW, Max Gain
 Noise (EIN):
 -124 dBu, 22 kHz BW, Max Gain,
 Rs = 150 Ω THD+N: < 0.02%
 Dynamic Range: 100 dB (non A-weighted)
 Crosstalk < -91 dB rel 17 dBu
 Sampling Rate: 48 kHz
 A/D - D/A Converters 24-bit

AUTO MIXER PARAMETERS

Number of Open Microphones (NOM)
 PA Adaptive Mode
 First Mic Priority Mode
 Last Mic Mode
 Maximum # of Mics Mode
 Ambient Level
 Gate Threshold Adjust
 Off Attenuation Adjust
 Hold Time
 Decay Rate

MATRIX MIXING PARAMETERS

8 Mic/Line Analog Inputs
 2 Line Inputs
 8 Line Outputs
 8 Line Mic/Line in Expansion with Optional INTERACT Pro 8i
 3 Assignable Processing Blocks IN/OUT

MICROPHONE INPUT PARAMETERS

Input Gain Adjust
 Mic or Line Level
 Phantom Power ON/OFF
 Echo Cancellation ON/OFF
 Noise Cancellation ON/OFF
 PEQ
 Filters
 Mute ON/OFF
 Chairman Override ON/OFF
 AGC ON/OFF
 Automatic Level Control ON/OFF
 Auto Gate/Manual Gate
 Adaptive Ambient ON/OFF

ASSIGNABLE PROCESSING BLOCKS

Channels: 3
 Filter Nodes: 4 Per Channel
 Filter Types: All Pass, Low Pass, High Pass, Low Shelving, High Shelving, PEQ, Notch
 Compressor: 1 Per Channel

MIC/LINE INPUTS 1-8

Impedance: 5 kΩ Per Leg or 10 kΩ Balanced
 Maximum Level: -65 dBu to +17 dBu
 Echo Cancellation:
 128 ms Tail Time (Works with 12 dB of Room Gain)
 Phantom Power: 24 VDC at 10 mA

LINE INPUTS 9-10

Impedance: 5 kΩ Per Leg or 10 kΩ Balanced
 Maximum Level: 17 dBu

LINE OUTPUTS 1-8

Impedance: 50 Ω Per Leg
 Nominal Level: 0 dBu
 Maximum Level: 17 dBu

TELEPHONE INTERFACE

Telephone Audio Performance
 Conditions: Unless otherwise specified, all measurements are performed with Transmit Limiter and Receive ALC disabled
 Frequency Response: 250 Hz to 3.3 kHz ± 1dB
 THD+N: < 0.30% re-max level 250 Hz to 3.3 kHz
 SNR: > 62 dB re-max level
 Telco Line Echo Cancellation
 Tail Time: 32 ms
 Null: 55 dB Nominal
 Telephone Noise Cancellation
 Noise Cancellation 6-15 dB Attenuation

RS-232 CONTROL PORT

DB9 female
 Baud Rates: 9,600 / 19,200 / 38,400 / 57,600 (default) / 115,200
 Protocol: 8-bit / 1 Stop / No Parity
 Hardware Flow Control ON(Default)/OFF

USB CONFIGURATION PORT

USB 2.0 Compatible
 Type: B Connector

LAN

10/100 Ethernet
 RJ-45 with Activity LED
 Supports: Telnet, HTTP

EXPANSION BUS IN/OUT

Cable:
 CAT5 Twisted Pair, Solid Conductor

Maximum Cable Length:
 Between INTERACT Pro & INTERACT Pro 8i:
 80 feet

Between INTERACT Pro/Pro 8i & INTERACT COM:
 80 feet

CONFIGURATION SOFTWARE

INTERACT Supports:
 Microsoft XP, Vista and Windows 7

INTERACT COM AND INTERACT COM-W (OPTIONAL)



USB AUDIO CHANNEL IN/OUT:
 USB 2.0 Compatible

Connector:
 Mini Type B IN/OUT Channel, 16-bit at 16 kHz

HEADSET AUDIO CHANNEL IN/OUT:
 Connector: RJ-9

Supported Telephone Sets:
 Most Cisco, Avaya, and Nortel phones

Audio Performance:
 Frequency Response: 40 to 3300 Hz THD and
 Noise: < 0.04% re-max level
 with 0 dB gain @ 1 kHz
 Dynamic Range: > 84 dB (non A-weighted)

Audio Processing:
 Receive Automatic Level Control
 Line Echo Cancellation for Side-tone
 Elimination

GPIO:
Pin 1: Global Mute (C)
Pin 2: Global Mute (S)
Pin 3: ON/OFF Hook (C)
Pin 4: ON/OFF Hook (S)
Pin 5: 5V DC up to 40 mA

COMMUNICATIONS:
 RS-232 Connected to Mixer

POWER SUPPLY
 Primary Voltage: 100 to 240 VAC
 Auto-Sensing, 50-60 Hz
 Power Consumption: 26 W max

DIMENSIONS (W X D X H)

INTERACT Pro: 17" x 7.5" x 2"
 (43.2 cm x 19.1 cm x 5.1 cm)
 INTERACT COM: 4.7" x 5.6" x 1.7"
 (11.9 cm x 14.3 cm x 4.4 cm)

WEIGHT

INTERACT Pro: 4.5 lbs. (2.25 kg)
 INTERACT COM: 1.51 lbs (0.75 kg)

COMPLIANCE

ROHS Compliant
 WEEE Compliant
 UL Safety Listed
 AES48-2005 AES Standard on Grounding and
 EMC Practice

OPTIONAL ACCESSORIES

INTERACT - COM
 910-154-030
 INTERACT Pro 8i Input Expander
 910-154-065

PART NUMBER

910-154-055

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way,
 Suite 500
 Salt Lake City, UT 84116

US & Canada

Tel: 801.975.7200
 TollFree: 800.945.7730
 Fax: 801.303.5711

International

Tel: +1.801.975.7200
 global@clearone.com

Sales

Tel: 801.975.7200
 sales@clearone.com

TechSupport

Tel: 801.974.3760
 tech.support@clearone.com